

Sea water self contained

Model	IFS1T-R4W	IFS2T-R4W	IFS3T-R4W	IFS5T-R4W
Daily Output (kg/24hrs.)	1,000	2,000	3,000	5,000
Refrigeration Capacity (kw)	6.64	11.96	19.0	31.9
Refrigerant	R404A	R404A	R404A	R404A
Power Consumption (kw)	5.25	8.2	13.2	22.4
Power Supply	3P-380/415V/50Hz	3P-380/415V/50Hz	3P-380/415V/50Hz	3P-380/415V/50Hz
Water Pressure	100-500kpa	100-500kpa	100-500kpa	100-500kpa
Water Pipe	1/2"	1/2"	1/2"	1/2"
Weight (kg)	500	600	650	1050
Dimensions (mm)	1320x920x900	1500x1100x1250	1500x1200x1350	1800x1500x1540

Model	IFS10T-R4W	IFS20T-R4W
Daily Output (kg/24hrs.)	10,000	20,000
Refrigeration Capacity (kw)	63.8	114.0
Refrigerant	R404A	R404A
Power Consumption (kw)	45.5	79.0
Power Supply	3P-380/415V/50Hz	3P-380/415V/50Hz
Water Pressure	100-500kpa	100-500kpa
Water Pipe	3/4"	2x 3/4"
Weight (kg)	2020	4410
Dimensions (mm)	3000x2050x1750	4000x2100x2200

Production capacities based on 25°C condenser water and 16°C sea water temperature
 Evaporator temperature -30°C
 Ice thickness 1.5—2.2mm

Continuing product improvement may necessitate changes of specifications without notice.