



Made in the US and supplied in Australia by Stuart Icemakers



100% Recyclable



The Kloppenberg Advantage

- Each shuttle system is shipped with a 48" ice paddle, 60" ice paddle is available
- Standard PCC250 cart(s) are included
- Capacities and crated weights include the cart(s) and are variable
- All Shuttle systems are shipped fully assembled, sleeves may be shipped separately
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	One Cart Model							
Model	Capacity	Width	Depth	Height	Weight			
SPS-1	500lbs	30"	36"	65"	320lbs			

- •SL denotes extended Sleeve—increases capacity by height ranging from 12" to 30"
- •G denotes Giant—increases capacity by adding 12" to the depth of the unit

	One Cart Model							
Model	Capacity	Width	Depth	Height	Weight			
SPS-1-G	900lbs	30"	48"	82"	370lbs			

- •SL denotes extended Sleeve—increases capacity by height ranging from 12" to 30"
- •G denotes Giant—increases capacity by adding 12" to the depth of the unit



SPS-1-G












- Each shuttle system is shipped with a 48" ice paddle, 60" ice paddle is available
- Standard PCC250 cart(s) are included
- Capacities and crated weights include the cart(s) and are variable
- All Shuttle systems are shipped fully assembled, sleeves may be shipped separately
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Two Cart Model						
Model	Capacity	Width	Depth	Height	Weight		
SPS-2	1500lbs	60"	36"	71"	530lbs		
SPS-2-SL	2500lbs	60"	36"	92"	690lbs		
SPS-2 Sleeve Only	1000lbs	60"	36"	30"	180lbs		

- •SL denotes extended Sleeve—increases capacity by height ranging from
- •G denotes Giant—increases capacity by adding 12" to the depth of the unit


**SPS-2 Sleeve** 



	Two Cart Model						
Model	Capacity	Width	Depth	Height	Weight		
SPS-2-G	1800lbs	60"	48"	71"	740lbs		
SPS-2-G-SL	3000lbs	60"	48"	101"	960lbs		
SPS-2G Sleeve Only	1200lbs	60"	48"	30"	280lbs		

- All stainless steel
- •SL denotes extended Sleeve—increases capacity by height ranging from 12" to 30"
- •G denotes Giant—increases capacity by adding 12" to the depth of the unit

**SPS-2G Sleeve** 







SPS-2-G







- Each shuttle system is shipped with a 48" ice paddle, 60" ice paddle is available
- Standard PCC250 cart(s) are included
- Capacities and crated weights include the cart(s) and are variable
- All Shuttle systems are shipped fully assembled, sleeves may be shipped separately
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis


	Three Cart Model						
Model	Capacity	Width	Depth	Height	Weight		
SPS-3	2000lbs	90"	36"	71"	950lbs		
SPS-3-SL	3400lbs	90"	36"	101"	1190lbs		
SPS-3 Sleeve Only	1400lbs	90"	36"	30"	400lbs		

- •All stainless steel
- •SL denotes extended Sleeve—increases capacity by height ranging from
- •G denotes Giant—increases capacity by adding 12" to the depth of the unit



	Three Cart Model						
Model	Capacity	Width	Depth	Height	Weight		
SPS-3-G	2400lbs	90"	48"	71"	1100lbs		
SPS-3-G-SL	4300lbs	90"	48"	101"	1570lbs		
SPS-3G Sleeve Only	1900lbs	90"	48"	30"	500lbs		

- All stainless steel
- •SL denotes extended Sleeve—increases capacity by height ranging from 12" to 30"
- •G denotes Giant—increases capacity by adding 12" to the depth of the





SPS-3-G



**SPS-3G Sleeve** 



- Standard cart(s) are included
- Capacities and crated weights include the cart(s) and are variable
- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

#### 36" Ice Fill Station (IFS900-125)

	Single Cart Model					
Model	Capacity	Width	Depth	Height	Weight	
IFS900-125	1069lbs	36"	34"	93.5"	360lbs	
IFS900-250	1069lbs	36"	34"	101"	380lbs	


- Seamless poly liner
- •Height includes 32.5" high square tube base on 125's and 41.5" on 250's
- •Standard ABS top for 34" deep units
- •-125 denotes a PCC125 cart
- •-250 denotes a PCC250 cart



48" Ice Fill Station (IFS1000-125)

	Single Cart Model						
Model	Capacity	Width	Depth	Height	Weight		
IFS1000-125	1161lbs	48"	34"	81.5"	380lbs		
IFS1200-125	1457lbs	48"	34"	93.5"	420lbs		
IFS1000-250	1161lbs	48"	34"	89"	400lbs		
IFS1200-250	1457lbs	48"	34"	101"	440lbs		

- Seamless poly liner
- •Height includes 32.5" high square tube base on 125's and 41.5" on 250's
- Standard ABS top for 34" deep units
- •-125 denotes a PCC125 cart
- •-250 denotes a PCC250 cart







- Standard cart(s) are included
- Capacities and crated weights include the cart(s) and are variable
- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

### 60" Ice Fill Station (IFS1300-125)

	Single Cart Model						
Model	Capacity	Width	Depth	Height	Weight		
IFS1300-125	1471lbs	60"	34"	81.5"	460lbs		
IFS1600-125	1846lbs	60"	34"	93.5"	510lbs		
IFS1800-125	2180lbs	60"	48"	82.5"	555lbs		
IFS2300-125	2725lbs	60"	48"	94.5"	610lbs		
IFS1300-250	1471lbs	60"	34"	89"	480lbs		
IFS1600-250	1846lbs	60"	34"	101"	530lbs		
IFS1800-250	2180lbs	60"	48"	90"	575lbs		
IFS2300-250	2725lbs	60"	48"	102"	630lbs		

- Seamless poly liner
- •Height includes 32.5" high square tube base on 125's and 41.5" on 250's
- Standard ABS top for 34" deep units
- •-125 denotes a PCC125 cart
- •-250 denotes a PCC250 cart









- Standard cart(s) are included
- Capacities and crated weights include the cart(s) and are variable
- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Double Cart Model						
Model	Capacity	Width	Depth	Height	Weight		
IFS1700-125	1818lbs	72"	34"	82.5"	665lbs		
IFS2400-125	2576lbs	72"	34"	102.5"	775lbs		
IFS2500-125	2639lbs	72"	48"	82.5"	780lbs		
IFS2700-125	3739lbs	72"	48"	102.5"	920lbs		
IFS1700-250	1818lbs	72"	34"	82.5"	685lbs		
IFS2400-250	2576lbs	72"	34"	102.5"	875lbs		
IFS2500-250	2639lbs	72"	48"	82.5"	800lbs		
IFS2700-250	3739lbs	72"	48"	102.5"	940lbs		

- Seamless poly liner
- •Height includes 32.5" high square tube base on 125's and 41.5" on 250's
- •Standard ABS top for 34" deep units
- •-125 denotes a PCC125 cart
- •-250 denotes a PCC250 cart

	Single Cart Model						
Model	Capacity	Width	Depth	Height	Weight		
IFS3500-125	3557lbs	96"	48"	82.5"	825lbs		
IFS3400-125	5039lbs	96"	48"	102.5"	1260lbs		
IFS4800-125	6522lbs	96"	48"	122.5"	1350lbs		
IFS3500-250	3557lbs	96"	48"	82.5"	845lbs		
IFS3400-250	5039lbs	96"	48"	102.5"	1280lbs		
IFS4800-250	6522lbs	96"	48"	122.5"	1370lbs		

- Seamless poly liner
- •Height includes 32.5" high square tube base on 125's and 41.5" on 250's
- •Standard ABS top for 34" deep units
- •-125 denotes a PCC125 cart
- •-250 denotes a PCC250 cart

## **72" Ice Fill Station (IFS1700-125)**



96" Ice Fill Station (IFS3500-125)



- All poly carts are designed for shuttle bins
- Center split hinged lids open to the cart sides
- Foot operated rear drain
- Handles on both ends of cart
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Ice Cart					
Model	Capacity Width Depth Height Weight					
PCC-125	125lbs	22"	29"	29"	75lbs	

- •Easily maneuvered 5" front and 10" rear castors
- Comes standard with all shuttle systems



	Ice Cart					
Model	Capacity	Width	Depth	Height	Weight	
PCC-250	250lbs	22"	30"	38"	100lbs	

- •Easily maneuvered 5" front and 10" rear castors
- Comes standard with all SPS systems and IFS-250's







# ICE STORAGE EQUIPMENT CARTS

#### **Common Features**

- Stainless steel exterior
- · Seamless poly-insulated liner
- Center split hinged lids open to the cart sides
- Hand style foot-operated drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Ice Cart				
Model	Capacity	Width	Depth	Height	Weight
CC-250	250lbs	24"	30"	38"	150lbs

•Rugged 5" Castors, (2) fixed, (2) swivel with brake



-	Ice Carts					
Model	Capacity	Width	Depth	Height	Weight	
CC-300	300lbs	24"	36"	34"	150lbs	

•Rugged 5" Castors, (2) fixed, (2) swivel with brake











- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring latch
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved

	Single Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
705-SS	741lbs	30"	34"	58"	240lbs	
705-SBB	741lbs	30"	34"	58"	240lbs	

- •SBB—Stainless steel front, sides, back and bottom
- •SS—Stainless steel front and sides
- Seamless poly liner

II. Diversitation	

705

905

	Single Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
905-SS	1023lbs	30"	34"	77"	285lbs	
905-SBB	1023lbs	30"	34"	77"	285lbs	

- •SBB—Stainless steel front, sides, back and bottom
- •SS—Stainless steel front and sides
- Seamless poly liner





- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved

	Single Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
965-SBB	1069lbs	36"	34"	67"	295lbs	

- •SBB—Stainless steel front, sides, back and bottom
- SS—Stainless steel front and sides
- Stainless steel liner



- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

			Single Door Upright					
Mod	el	Capacity	Width	Depth	Height	Weight		
1045-	SS	1161lbs	48"	34"	55"	280lbs		
1045-9	SBB	1161lbs	48"	34"	55"	280lbs		

- •SBB—Stainless steel front, sides, back and bottom
- •SS—Stainless steel front and sides
- Seamless poly liner



	Single Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
1315-SS	1457lbs	48"	34"	67"	320lbs	
1315-SBB	1457lbs	48"	34"	67"	320lbs	

- •SBB—Stainless steel front, sides, back and bottom
- •SS—Stainless steel front and sides
- Seamless poly liner









- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Single Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
1325-SS	1471lbs	60"	34"	55"	310lbs	
1325-SBB	1471lbs	60"	34"	55"	310lbs	

- •SBB—Stainless steel front, sides, back and bottom
- •SS—Stainless steel front and sides
- Seamless poly liner



		Single Door Upright					
Model	Capacity	Width	Depth	Height	Weight		
1665-SS	1846lbs	60"	34"	67"	370lbs		
1665-SBB	1846lbs	60"	34"	67"	370lbs		

- •SBB—Stainless steel front, sides, back and bottom
- •SS—Stainless steel front and sides
- Seamless poly liner







- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Single Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
1915-SBB	2180lbs	60"	48"	56"	400lbs	

- All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and
- Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.



	Single Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
2415-SBB	2725lbs	60"	48"	68"	525lbs	

- All stainless steel
- •Sleeve is W x D x 12"H
- •Sleeves can be customized to add height, special doors and more
- •Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.









- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Double Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
1455	1818lbs	72"	34"	56"	470lbs	

- All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and more
- •Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.

ROPPENSERS
T

1415

	Double Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
2215	2576lbs	72"	34"	76"	625lbs	

- All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and
- Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.





ISE ADVANTAGE by Kloppenberg



- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Double Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
2115	2639lbs	72"	48"	56"	600lbs	

- •All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and more
- Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.



		Double Door Upright					
Model	Capacity	Width	Depth	Height	Weight		
3225	3739lbs	72"	48"	76"	785lbs		

- All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and
- Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.









- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Double Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
4325	4839lbs	72"	48"	96"	980lbs	

- •All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and more
- •Sleeves are shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.





- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Double Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
2845	3557lbs	96"	48"	56"	730lbs	

- All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and more
- •Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.



	Double Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
4345	5039lbs	96"	48"	76"	1200lbs	

- All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and
- •Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.









- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- Stainless steel baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

	Double Door Upright					
Model	Capacity	Width	Depth	Height	Weight	
5835	6522lbs	96"	48"	96"	1300lbs	

- All stainless steel
- •Sleeves are W x D x 20"H and have a view window
- •Sleeves can be customized to add height, special doors and more
- •Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.



5835



# ICE STORAGE EQUIPMENT

# **UPRIGHT: PRISON PACKAGE**

#### Single Door Upright—Prison Package Model Width Capacity Depth Height Weight 705\* 741 lbs 30" 34" 58" 240 lbs 905\* 1023 lbs 30" 34" 77" 285 lbs 965 1069 lbs 36" 34" 67" 295 lbs 1045\* 1161 lbs 48" 34" 55" 280 lbs 1315\* 1457 lbs 48" 34" 67" 320 lbs 1325\* 1471 lbs 60" 34" 55" 310 lbs 1665\* 1846 lbs 60" 34" 67" 370 lbs 1915 2180 lbs 60" 48" 56" 400 lbs 2725 lbs 60" 48" 525 lbs 2415

- •\*Denotes poly liners. Otherwise stainless steel.
- •Sleeves are W x D x 20"H
- Sleeves can be customized to add height, special doors and more
- •Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.

	Double Door Upright—Prison Package						
Model	Capacity	Width	Depth	Height	Weight		
1415	1818 lbs	72"	34"	56"	470 lbs		
2115	2639 lbs	72"	48"	56"	600 lbs		
2215	2576 lbs	72"	34"	76"	625 lbs		
2845	3557 lbs	96"	48"	56"	730 lbs		
3225	3739 lbs	72"	48"	76"	785 lbs		
4325	4839 lbs	72"	48"	96"	980 lbs		
4345	5039 lbs	96"	48"	76"	1200 lbs		
5835	6522 lbs	96"	48"	96"	1300 lbs		

- •All stainless steel
- Sleeves are W x D x 20"H
- •Sleeves can be customized to add height, special doors and more
- Sleeves may be shipped separate
- •Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.

#### **Common Features**

- 20 gauge stainless steel liner
  - Seamed or fully welded
- Stainless steel snout with lockable door
- Stainless steel top closure
- 6" stainless steel bolt down flanged legs
- Stainless steel view window cover plate
- Security fasteners for authorized removal

705



2115





